Pocket Door System



Eclipse Pocket Door

- · Cam assisted door extraction
- Cushioned door insertion
- Soft closing and soft opening buffer
- Slide in movement facilitates installation/removal of mechanism from front
- Quick coupling hinges
- Suits doors from 18mm to 30mm thickness
- Suits door widths from 400mm to 900mm
- Suits door heights from 2200mm to 2500mm
- Door adjustment (all accessible from front of cabinet):

Vertical: +4mm/-1mm
Horizontal: ±2mm
Front: ±4m

- Many applications in kitchens, laundries, bathrooms, offices
- Internal pocket width 55mm

Item Code	Description	Sales Unit
SAL521	Pocket Door, Left Hand Door	Ea
SAL522	Pocket Door, Right Hand Door	Ea

MADE TO ORDER - Contact us for an order form

Calculations for Minimum Structure Dimensions

Usable structure depth (PSU - mm)												
	400 - 500		501	- 600	601 - 700		701 - 800		801 - 900			
Door height HA (mm)	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
	1546	1696	1668	1757	1790	1879					3 x	max 18 kg
	1697	2091	1758	2152	1880	2213	2002	2274	2124	2335	4 x	max 24 kg
	2092	2500	2153	2500	2214	2500	2275	2500	2336	2500	5 x	max 30 kg

SALICE





